

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** Adhesion promoter PP
- **Article number:** Series 700-PP
- **Application of the substance / the preparation** Additive

SUPPLIER: Colour Components
24 / 25 Ingleston Rd, Tingalpa QLD 4173
Tel: 1300 196 156 email: mail@colourcomponents.com.au

Emergency Information Tel: 1300 196 156
Poisons Information Centre Hotline
13 11 26 (Australia)
0800 764 766 (New Zealand)

2 Hazards identification

- **Hazard description:**









Xn Harmful

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
R 20/21 Harmful by inhalation and in contact with skin.
R 38 Irritating to skin.
R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7	xylene	 Xn,  Xi; R 10-20/21-38	50-100%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene	 Xn,  F; R 11-20	10-25%
CAS: 108-90-7 EINECS: 203-628-5	chlorobenzene	 Xn,  N; R 10-20-51/53	2.5-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Trade name: Adhesion promoter PP

(Contd. of page 1)

- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	------------------------------------------------------------------------------------------------------------------

(Contd. on page 3)

Trade name: Adhesion promoter PP

(Contd. of page 2)

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm

108-90-7 chlorobenzene

WEL Short-term value: 3 ppm
Long-term value: 1 ppm
Sk

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

General Information

Form: Fluid
Colour: Transparent
Odour: Characteristic

Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

(Contd. on page 4)

Trade name: Adhesion promoter PP

(Contd. of page 3)

· Flash point:	28°C (Abel Pensky)
· Ignition temperature:	430°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.0 Vol %
Upper:	7.8 Vol %
· Vapour pressure at 20°C:	9.5 hPa
· Density at 20°C:	0.955 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Viscosity:	
Dynamic at 20°C:	150 mPas
VOC (EC)	75.00 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

108-90-7 chlorobenzene

Oral	LD50	2290 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

GB

(Contd. on page 5)

Trade name: Adhesion promoter PP

(Contd. of page 4)

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
 - **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|----------|------------------------------------------------------------|
| 07 07 04 | other organic solvents, washing liquids and mother liquors |
|----------|------------------------------------------------------------|
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1210
- **Packaging group:** III
- **Hazard label:** 3
- **Description of goods:** 1210 PRINTING INK RELATED MATERIAL

- **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1210
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-D
- **Marine pollutant:** No
- **Proper shipping name:** PRINTING INK RELATED MATERIAL

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3


(Contd. on page 6)

Trade name: Adhesion promoter PP

(Contd. of page 5)

- **UN/ID Number:** 1210
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** PRINTING INK RELATED MATERIAL

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
 Xn Harmful
- **Hazard-determining components of labelling:**
xylene
chlorobenzene
- **Risk phrases:**
10 Flammable.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Safety phrases:**
9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
23 Do not breathe fumes/aerosol.
25 Avoid contact with eyes.
36/37 Wear suitable protective clothing and gloves.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
10 Flammable.
11 Highly flammable.
20 Harmful by inhalation.
20/21 Harmful by inhalation and in contact with skin.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Department issuing MSDS:** Product safety department
- **Contact:**
Richard Gähwiler
richard.gaehwiler@printcolor.ch

GB